

Date _____

Customer code C- _____

Invoice address _____

Contact person _____

Your reference _____

Other delivery address _____

Invoice address = delivery address

Quote

= Standard equipment

DECON E-MOVE



Please add order form for the standard chair. Decon E-Move is compatible with all manual Netti wheelchairs. Mounting on the Netti wheelchair is included – the standard wheels will remain with the manufacturer.

Item nr.	Description	Price in €
D70002	<input checked="" type="checkbox"/> Decon E-Move with standard configuration as stated below and Netti adaptors	5.445,-
Battery and charger		
Standard	<input checked="" type="checkbox"/> NiMH battery with a max range of approx. 20 km	0,-
D70012	<input type="checkbox"/> Li-ion battery with a max range of approx. 35 km	679,-
Standard	<input checked="" type="checkbox"/> Battery charger	0,-
D70022	<input type="checkbox"/> Power converter for car	114,-
User weight		
Standard	<input checked="" type="checkbox"/> Max user weight 130 kg	0,-
D70032	<input type="checkbox"/> Heavy duty version - max user weight 150 kg Rims and spokes are made from a stronger material	145,-
Wheel size		
D72001	<input type="checkbox"/> 20" fine tread pneumatic wheels with stainless steel push rims	156,-
D72002	<input type="checkbox"/> 22" fine tread pneumatic wheels with stainless steel push rims	10,-
Standard	<input checked="" type="checkbox"/> 24" fine tread pneumatic wheels with stainless steel push rims	0,-
D72003	<input type="checkbox"/> 26" fine tread pneumatic wheels with stainless steel push rims (only for Netti III family)	156,-

Tyres			
Standard	<input checked="" type="checkbox"/>	Fine tread pneumatic wheels	0,-
D72004	<input type="checkbox"/>	PU wheels	38,-
Push rims and spoke guards			
Standard	<input checked="" type="checkbox"/>	Stainless steel push rims	0,-
D72005	<input type="checkbox"/>	Poly compact push rims	72,-
D72006	<input type="checkbox"/>	Poly gel push rims	98,-
D72007	<input type="checkbox"/>	Max grip push rims	178,-
D72008	<input type="checkbox"/>	Transparent spoke guards	106,-
Programs			
D72009	<input type="checkbox"/>	Second profile With this option, there is an extra button on the wheelchair. You can switch between two pre-programmed settings, which you can define yourself. For example, for inside and outside driving.	399,-
Flex handles			
Standard	<input checked="" type="checkbox"/>	Power switch	0,-
D72010	<input type="checkbox"/>	Power switch Flex handle to make it easier to reach the switch, 150 mm	440,-
D72011	<input type="checkbox"/>	Power switch Flex handle to make it easier to reach the switch, 210 mm	459,-
D72013	<input type="checkbox"/>	Second profile switch Flex handle to make it easier to reach the switch, 150 mm	449,-
D72014	<input type="checkbox"/>	Second profile switch Flex handle to make it easier to reach the switch, 210 mm	469,-
Mounting of battery			
Standard	<input checked="" type="checkbox"/>	Behind the back of the wheelchair, including bag for mounting	0,-
Netti wheels			
D70013	<input type="checkbox"/>	Delivery with standard Netti mail wheels for wheel combination 24"+7" incl. quick release and bushers (a constant change between Decon and Netti wheels is only possible as special adaptation)	59,-
D800	<input type="checkbox"/>	Delivery with standard Netti mail wheels for other wheel combinations than 24"+7" incl. quick release, bushers and other necessary parts (a constant change between Decon and Netti wheels is only possible as special adaptation)	Price on request

Specifications

Motor	Yamaha motors: AC servomotor, 24V 110W
Battery types	NiMH, 24 V, 6.7 Ah, (160.8 Wh) range 20 km Li-ion, 25 V, 11.8 Ah (280 Wh) range 35 km
Wheel	7 kg
Total weight	17 kg (including NiMH battery) 18 kg (including Li-ion battery)
Total chair width	Netti 4U CED: Seat width approx. + 220 mm Netti III Family: Seat width approx. + 260 mm E-Move increases the total width with approx. 40 mm
Wheel dimensions	20", 22", 24" or 26"
Air pressure	6 Bar, 600 kPa
Speed	0–6 km/h
Maximum range with fully charged battery	Approx. 20 km with NiMH battery Approx. 35 km with Li-ion battery in accordance with ISO 7176-4
Fuse	30A (flat)
Max user weight	130 kg
Max user weight "Heavy-duty"	150 kg
Max gradient	6°
CE mark	Complies with EU-Directive 93/42/EEC
Battery charger	100 to 240V AC, 50/60H
Estimated effect	37V 26A (when charging)
Rated power charging time	Normal charging time approx. 2–3 hours NiMH & Li-ion. Service charge NiMH: 3-13 hours, full capacity (once every 13-26 charges)
Possible combinations	Please send us a request for a combination with other options of the selected wheelchair as some combinations might not be possible.